



WELES LED



LED GROW
LIGHTING




WLA-720W-FS



One **WELES** WLA-720W-FS fixture contains eight light bars each 90W.

ADVANTAGES OF WELES LED Grow Lighting



Our **Full Spectrum** is an enriched white spectrum that takes the best of HPS and Metal Halide strategies and improves upon them by boosting the red and blue wavelengths. Designed to grow the way you're used to, without the high energy bill.

Fixture Specifications	
Typical Photon Flux (PPF)	1870 $\mu\text{mol/s}$
Efficiency (PPE)	2.6 $\mu\text{mol/J}$
AC Input Power	720 Watt
AC Input Voltage	90-277V, 50/60Hz
Dimming Range	25-50-75-100%
Light Distribution	120°
Operating Temperature	-10 - 40 C
IP Rating	IP 65
LED Chip	Osram
Wavelength	3000K + 6000K + 660nm
Material	Aluminium
Net Weight	8.4 kg
Dimensions LxWxH	1160 x 1160 x 50 mm
Working Lifetime	50.000 hours
Warranty	3 years

Max Input Amperage by Voltage Service

Voltage	90V	180V	240V	277V
Amperage	8.8A	4.4A	3.3A	2.85A




weles.global



OSCONIQ S 3030



High Transmittance Waterproof Coating



Surface Temperature is below 60 C



Long lifespan, Independent driver



Complies with TR CU 020/2011; TR CU 004/2011

«WELES» Group of Companies
 Address: Chotešovská 680/1, 190 00, Praha, Czech Republic
 Tel: +420 77 856 34 86
 office@weles.global